

This safety data sheet has been prepared in accordance with the requirements of EC Directives 1999/45/EC and 2001/58/EC and provides information relating to the safe handling and use of the product.

## 1. PRODUCT AND COMPANY INFORMATION

<b>Product Code</b>	0209001
<b>Trade Name</b>	Super Lube Oil with Teflon (Aerosol)
<b>Manufacturer/Supplier</b>	Henkel Loctite Adhesives Ltd.
<b>Address</b>	Watchmead, Welwyn Garden City, Herts., AL71JB. UK
<b>Phone Number</b>	01 707 358800
<b>Fax Number</b>	01 707 358900
<b>Emergency Phone Number</b>	+353-1-4599301/+353-87-2629625/+353-1-4046444

Supplied by: RS Components Ltd. Birchington Road, Corby, Northants, NN17 9RS. Tel: (01536) 402888
--

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

Nature	Lubricant			
<b>Hazardous Components in Product for EC</b>				
Component Name	CAS / EINEC	Concentration	R Phrases	Classification
CO2 Propellant	124-38-9 204-696-9	1.00 - 5.00		
N-Heptane	142-82-5 205-563-8	30.00 - 60.00	R11, R38, R65, R67, R50/53	F, Xn, N

## 3. HAZARD IDENTIFICATION

This product is highly flammable. Irritating to skin. Vapours may cause drowsiness and dizziness. Solvent will have a defatting action on the skin making it more susceptible to dermatitis and sensitisation. Inhalation of vapours may cause headaches or dizziness. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 4. FIRST AID MEASURES

### First Aid - Inhalation

Remove affected person to fresh air, and if still feeling unwell seek medical attention.

### First Aid - Skin

Wash with plenty of soap and water. If irritation persists, seek medical advice.

### First Aid - Eyes

Flush eyes with plenty of water for at least 15 minutes. If irritation persists seek medical attention.

### First Aid - Ingestion

Rinse mouth with water then give plenty of water to drink. Do not induce vomiting. Seek medical advice.

## 5. FIRE FIGHTING MEASURES

This product is highly flammable having a flash point of <0°C. If product is involved in fire extinguish with dry powder, foam or carbon dioxide. Self contained breathing apparatus should be worn when dealing with fire. Aerosol containers may explode when exposed to high temperatures. Keep unaffected containers cool with water spray.

## 6. ACCIDENTAL RELEASE MEASURES

Contain spillage, and absorb onto an inert absorbent such as sand or multisorb and place in a sealed container for supervised disposal. Wash spillage site thoroughly with detergent and water.

---

**7. HANDLING AND STORAGE**

---

**Handling**

Good industrial hygiene practices should be observed. In circumstances where there is a potential for prolonged or repeated skin contact, the use of disposable gloves (polyethylene, natural rubber or equivalent ester-resistant material) is recommended.

**Storage**

Keep in a cool, well-ventilated area.

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

**Occupational exposure limits****CO2 Propellant**

ACGIH: STEL 3000ppm 15min TWA.

ACGIH: TLV 5000ppm 8h TWA.

HSA (2002).C.O.P.: OEL 5000 ppm,(9000 mg/m<sup>3</sup>) 8h  
TWAHSA (2002).C.O.P.: OEL 15000 ppm,(27000 mg/m<sup>3</sup>) 15  
min exposure limit.**N-Heptane**

ACGIH: TLV 400ppm 8h TWA.

ACGIH: STEL 500ppm 15min TWA.

HSA (2002).C.O.P.: OEL 500 ppm,(2000 mg/m<sup>3</sup>) 15  
min exposure limit.HSA (2002).C.O.P.: OEL 400 ppm,(1600 mg/m<sup>3</sup>) 8h  
TWA

Good industrial hygiene practices should be observed. In circumstances where there is a potential for prolonged or repeated skin contact, the use of disposable gloves (polyethylene, natural rubber or equivalent ester-resistant material) is recommended. Use in well ventilated area. Safety glasses should be worn.

---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

---

<b>Physical State</b>	Aerosol.
<b>Colour</b>	White.
<b>Odour</b>	Characteristic.
<b>pH</b>	Not applicable.
<b>Boiling Range/Point (°C)</b>	No data.
<b>Flash Point (CC) (°C)</b>	< 0
<b>Specific Gravity</b>	Data not available.
<b>Solubility in Water (kg/m<sup>3</sup>)</b>	Insoluble.
<b>Solubility in Acetone</b>	Not listed.
<b>Vapour Pressure (mmHg @25°C)</b>	No data.
<b>Explosion Limits (%)</b>	No data.

---

**10. STABILITY AND REACTIVITY**

---

Stable under normal conditions.

---

**11. TOXICOLOGICAL INFORMATION**

---

**Inhalation**

Inhalation of vapours may cause headaches or dizziness.

---

**11. TOXICOLOGICAL INFORMATION**

---

**Skin**

May cause irritation to skin. Solvent may remove essential oils from the skin making it susceptible to attack from other chemicals.

**Eyes**

May cause irritation to the eyes.

**Ingestion**

This product is considered to be of low toxicity having an acute oral LD50 (rat) >2000mg/kg by analogy to other similar products.

---

**12. ECOLOGICAL INFORMATION**

---

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product should not go into drains or surface water.

---

**13. DISPOSAL CONSIDERATIONS**

---

Dispose of in accordance with local and national regulations.

---

**14. TRANSPORT INFORMATION**

---

<b>UN Number</b>	1950
<b>Air (IATA)</b>	Aerosols, flammable, Class 2.1
<b>Sea (IMO)</b>	Aerosols, Class 2 EmS F-D S-U .
<b>Road (ADR)/Rail (RID)</b>	Aerosols, Class 2 Classification code: 5F

---

**15. REGULATORY INFORMATION**

---

**Contains**

N-Heptane

**Labelling Information**

Highly flammable



Irritant



Dangerous for the Environment

**R phrases**

R11 Highly flammable.  
R38 Irritating to skin.  
R67 Vapours may cause drowsiness and dizziness.  
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
S16 Keep away from sources of ignition - No Smoking.  
S23 Do not breathe vapour.  
S28 After contact with skin, wash immediately with plenty of soap and water. S51 Use only in well ventilated areas.

**S phrases****Voluntary Labelling**

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding +50°C.  
Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material.

---

**16. OTHER INFORMATION**

---

**MSDS data revised** 10 July 2003

**Hazardous Components in Product for EC****Component Name**CO2 Propellant  
N-HeptaneR11  
R38  
R50/53R65  
R67R11 Highly flammable.  
R38 Irritating to skin.  
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65 Harmful: may cause lung damage if swallowed.  
R67 Vapours may cause drowsiness and dizziness.**R Phrases**R11, R38, R65,  
R67, R50/53

Prepared by:

Dr. Paul Friery  
Senior HRA Specialist  
Health & Regulatory Affairs - Europe

Further Information may be obtained from:-

Loctite Corporation,  
Health and Regulatory Affairs - Europe,  
Tallaght Business Park,  
Whitestown,  
Dublin 24,  
Ireland.Tel: +353-1-4046444.  
Fax: +353-1-4510806.

The information in this safety data sheet was obtained from reputable sources and to the best of our knowledge is accurate and current at the mentioned date. Neither Loctite nor its subsidiary companies accept any liability arising out of the use of the information provided here or the use, application or processing of the product(s) described herein. Attention of users is drawn to the possible hazards from improper use of the product(s). This safety data sheet was prepared in accordance with Commission Directive 2001/59/EC adapting to technical progress for the 28th time Council Directive 67/548/EEC and Commission Directive 1999/45/EC.